

Use and Care Instructions

Ice Maker

Durable, Portable, Convenient



TABLE OF CONTENTS

IMPORTANT SAFETY INSTRUCTIONS	2
PREPARING YOUR ICE MAKER FOR USE	
IMPORTANT SAFETY TIPS	3
GETTING TO KNOW YOUR UNIT	4
OPERATING PROCEDURES & MAINTENANCE	
UNPACKING YOUR ICE MAKER	5
CONNECTING YOUR ICE MAKER	5
CLEANING AND MAINTAINING YOUR ICE MAKER	5
USING YOUR ICE MAKER	
START TO MAKE THE ICE-CUBE	6
TIMER SETTING	6
CLOCK DISPLAY & THE CORRECT TIME	7
CLEANING REMINDING	7
TROUBLESHOOTING	8
TECHNICAL PARAMETERS & CIRCUIT DIAGRAM	
TECHNICAL SPECIFICATION	8
CIRCUIT DIAGRAM	9

IMPORTANT SAFETY INSTRUCTIONS

Your safety and the safety of others are very important.

We have provided many important safety messages manual and your appliance. Always read and obey all safety massages.

This is the safety alert symbol:



All safety messages will follow the safety alert symbol and the word "DANGER" or "WARNING".



WARNING

These words mean:

You can be killed or seriously injured if you don't immediate follow instructions.

All safety messages will tell you what the potential hazard is, tell you how to reduce the chance of injury, and tell you what can happen if the instructions are not followed.

IMPORTANT SAFETY TIPS

PREPARING YOUR ICE MAKER FOR USE

When using electrical appliances, basic safety precautions should be followed to reduce the risk of fire, electric shock, and injury to persons or property. Read all instructions before using any appliance.

- Do not operate this, or any other appliance with a damaged cord.
 Connect to properly polarized outlets only. No other appliance should be plugged into the same outlet. Be sure that the plug is fully inserted into the receptacle.
- Do not run the power cord over carpeting or other heat insulators. Do not cover the cord.
 Keep cord away from traffic areas, and do not submerge in water.
- We do not recommend the use of an extension cord, as it may overheat and become a risk
 of fire. If you must use an extension cord, use No.14 AWG minimum size and rated no less
 than 1875 watts.
- Unplug the ice maker before cleaning or making any repairs or servicing.
- Exercise caution and use reasonable supervision when appliance is used near children.
- Do not use your ice-maker outdoors. Place the ice-maker away from direct sunlight and make sure that there is at least 4 inches of space between the back of your unit and wall.
 Keep a minimum distance of 4 inches on each side of your unit free.
- Do not use other liquid to make the ice-cube other than water.
- Do not clean your ice maker with flammable fluids. The fumes can create a fire hazard or explosion.
- Do not tip over.
- If the ice maker is brought in from outside in wintertime, give it a few hours to warm up to room temperature before plugging it in.

WARNING: This appliance must be earthed.

IMPORTANT:

The wires in this mains lead are colored in accordance with the following code:

Green or Green with a strip yellow: Grounding White: Neutral Black: Live

To avoid a hazard due to instability of the appliance, it must be placed at a even or flat surface.


GETTING TO KNOW YOUR UNIT

- 1. Cover: With a transparent window to allow interior visibility.
- 2. Ice scoop.
- 3. Ice shovel.
- 4. Control Panel: Easy to use, visible functions and LCD display setting.
 - A. LCD display window.
 - 1: Current Clock Time
 - 2: No water diplay, When flashing, means no water in the unit, need to pour water in.
 - 3. Ice-full display, when it display, means the ice basket is full of ice-cube.
 - 4. ON/OFF display, if the unit has been turned off, this symbol will flash; And if the unit is turned on, this symbol will always display.
 - 5.Clean symbol: when this symbol flashs, means the unit need to be cleaned.
 - 6.Ice-cube size displaying: Small, Medium, and Large.
 - 7. Timer delay time display.
 - B. ON/OFF button: To start or stop the unit.
 - C. SELECT button: To select your desired size of the ice-cube:

small, medium, large, three size of the ice-cube can be selected.

Or to change the time digit during the clock or timer setting program.

- D. CLOCK button: To set the displayed time to the correct current time.
- E. TIMER button: To set or cancel the timer program to let the unit start to run at your desired time or stop the unit at your desired because of forgetting.
- 5. Water drain cap: For draining water from water reservoir.
- 6. Air Outlet
- 7.Ice basket



UNPACKING YOUR ICE MAKER

OPERATING PROCEDURES & MAINTENANCE

- 1. Remove the exterior and interior packaging. Check that ice basket and ice scoop is included. If any parts are missing, please contact our customer service.
- 2. Clean the interior with lukewarm water and a soft cloth. Take out the ice basket and clean it
- Find a location for your ice maker that is protected from direct sunlight and other sources of heat (i.e.: stove, furnace, radiator). Place the ice maker on a level surface. Maker sure that there is at least 4 inches of space between the back and sides of your ice maker and the wall.
- 4. Allow one hour for the refrigerant fluid to settle before plugging ice maker in.
- 5. The appliance must be positioned so that the plug is accessible.

CONNECTING YOUR ICE MAKER

DANGER

- * Improper use of the grounded plug can result in the risk of electrical shock. If the power cord is damaged please call our customer service.
- 1. This unit should be properly grounded for your safety. The power cord of this appliance is equipped with a three-prong plug which mates with standard three prong wall outlets to minimize the possibility of electric shock.
- Plug your appliance into an exclusive, properly installed, grounded wall outlet. Do not under any circumstances, cut or remove the third (ground) prong from the power cord. Any questions concerning power and/or grounding should be directed toward a certified electrician.
- 3. This appliance requires a standard 110-120volt, 60Hz electrical outlet with three-prong ground.


CLEANING AND MAINTAINING YOUR ICE MAKER

Before using your ice maker, it is strongly recommended to clean it thoroughly.

- 1. Take out the ice basket.
- 2. Clean the interior with diluted detergent, warm water and a soft cloth.
- 3. Then use the water to rinse the inside parts, and drain out the water by unplugging the drain cap on the side.
- 4. The outside of the ice maker should be cleaned regularly with a mild detergent solution and warm water.
- 5. Dry the interior and exterior with a soft cloth.
- 6. When the machine is not in use for a long time, open water drained cap to drain water completely from water reservoir.

USING YOUR ICE MAKER

- 1. Open the cover, remove the ice basket and pour water into water reservoir. Keep water level below the level mark.
- 2. Press "ON/OFF" button on the control panel to turn on the unit to begin the ice making cycle.
- 3. Select the size of the ice cube by pressing the "Select" button. Three sizes: SMALL, MEDIUM or LARGE can be selected:



If the room temperature is lower than 60°F, it is recommended to select the small or medium ice sign button in order to avoid ice sticking together.

- 4. The ice making cycle lasts 6 to 15 minutes, depending on the size of the ice cube selection and the ambient temperature. In the extreme hot room temperature, ice-making time maybe vary a lot.
- 5. While the icemaker is on, verify water level periodically. If water pump can't inject water, the

ice maker will stop automatically, and the "" symbol will flash in LCD display window. Fill water up to the level mark and press "ON/OFF" button two times again to turn on the unit again. Allow the refrigerant liquid inside the compressor at least 3 minutes to settle before restarting.

- 6. The ice maker automatically stops working when the ice basket is full and the " symbol will display in the LCD display widow.
- 7. Change water in the water reservoir every 24 hours to ensure a reasonable hygiene level. If unit isn't in use, drain all water left in the tank.

TIMER SETTING

Timer Delay Time Range: 0.5-19.5 hours.

Default Delay Time: 3 hours.

When the unit is running, you can set the unit with OFF-TIMER to let the unit stop running after your set delay time.

And when the unit is stopped, you can set the unit with ON-TIMER to let the unit start to run automatically after your set delay time, then when you go back home or have a dinner, you can enjoy the happy life that this ice-maker give to you.


How to set the timer

Press the TIMER button first, the default "3.0H" delay time will flash in LCD display window, then press the SELECT button to select your desired delay time. Each press SELECT button one time, the flashing delay time will increase 0.5 hour, and if you always press the SELECT button for mor than 3 seconds, the delay time will change very quickly. Then after 5 seconds flashing, the delay time digit will change from flashing to always displaying, means the timer program has been set.

How to cancel the timer

When the unit has been set with the timer or during the timer setting process, press the TIMER button, then the delay time digit will disappear, mean the timer set has been cancelled.

CLOCK DISPLAY & THE CORRECT TIME



This unit is supplied with CLOCK dipalying function.

If the displayed time is not correct, you can adjust it to the correct digit through the CLOCK and SELECT button.

First press the CLOCK button once, the digit meaning hour will start to flash first, then you can press SELECT button to change it, each press will increase 1 hour. Press the CLOCK button again, the digit meaning minute then will start to flash, and also press the SELECT to change it. Then press the CLOCK the third time to confirm it, and now it display the new correct clock. And during adjusting process, after 5 seconds flashing, the digit will automaticall change to always displaing, also means the new clock has been set.

CLEANING REMINDING

When the symbol flashs, means the unit need to be cleaned. And if you have cleaned the unit, always press the TIMER button for more than 5 seconds, this symbol will disappear from the LCD display window. And the cleaning timer will reset to Zero and reaccount again.

PROBLEM	POSSIBLE CAUSE	SOLUTION
Symbol " flashs.	Lack of Water.	Stop the ice maker, fill water, and press "ON/OFF" button again to restart the unit.
Symbol" " display in LCD display window.	There is too much ice.	Remove ice from ice basket.
Ice cubes stick together.	The ice cycle is too long.	Stop the ice maker, and restart it when the ice blocks melt. Select the small size ice cube selection.

TROUBLESHOOTING				
	Water temperature in inner tank is too low.	Change the water in the inner Tank. Temperature of water is better set between 45°F-90°F.		
Ice making cycle is normal	Ambient temperature or water temperature in inner tank is too high.	Please run the ice maker below 90°F and pour colder water into tank.		
but no ice is made.	Refrigerant liquid leakage.	Verify by a qualified technician. Verify by a qualified technician.		
	Pipe in the cooling system is blocked.			

TECHNICAL SPECIFICATION & CIRCUIT DIAGRAM

TECHNICAL SPECIFICATION		
Model	HZB-12	HZB-12/S
Protection Type	1	l
Power	115V/60Hz	115V/60Hz
Ice Making Current	1.9A	1.9A
Ice Harvest Current	2.7A	2.7A
Refrigerant	R134a/65g	R134a/65g
Design Pressure		
High Side	290Psig	290Psig
Low Side	88Psig	88Psig
Net Weight	12.0Kg	12.4Kg
Enclosure	Plastic	stainless steel

CIRCUIT DIAGRAM

